

1. (Five Times Amended) An ultrasonic motor, comprising: a movable member disposed to undergo movement in response to a drive force; a substrate having a conductor pattern for conveying a drive signal from a drive circuit; a piezoelectric vibrator provided on the substrate for undergoing oscillating movement in response to the drive signal so as to contact the movable member and generate the drive force to drive the movable member; and a support member provided on the substrate for mechanically fixedly supporting the piezoelectric vibrator at a point corresponding to a node of vibration of the piezoelectric vibrator on the substrate and transmitting the drive signal from the conductor pattern to electrodes of the piezoelectric vibrator so that no conductor wires extend from the substrate to connect the drive circuit and the piezoelectric vibrator.

3. (Twice Amended) An ultrasonic motor, comprising: a movable member disposed to undergo movement in response to a drive force; a substrate having a conductor pattern for conveying a drive signal from a drive circuit; a piezoelectric vibrator provided on the substrate for undergoing oscillating movement in response to the drive signal so as to contact the movable member and generate the drive force to drive the movable member; and a support member provided on the substrate for mechanically supporting the piezoelectric vibrator on the

substrate and transmitting the drive signal from the conductor pattern to electrodes of the piezoelectric vibrator so that no conductor wires extend from the substrate to connect the drive circuit and the piezoelectric vibrator, the support member having a constriction portion that is thinner than a connection portion connected to the piezoelectric vibrator.

5. (Twice Amended) An ultrasonic motor, comprising: a movable member disposed to undergo movement in response to a drive force; a substrate having a conductor pattern for conveying a drive signal from a drive circuit; a piezoelectric vibrator provided in a recess provided on the substrate for receiving the piezoelectric vibrator, the piezoelectric vibrator for undergoing oscillating movement in response to the drive signal so as to contact the movable member and generate the drive force to drive the movable member; and a support member provided on the substrate for mechanically supporting the piezoelectric vibrator on the substrate and transmitting the drive signal from the conductor pattern to electrodes of the piezoelectric vibrator so that no conductor wires extend from the substrate to connect the drive circuit and the piezoelectric vibrator; wherein the substrate has a recess portion for receiving the piezoelectric vibrator.

22. (Amended) An ultrasonic motor, comprising: a movable member disposed to undergo movement in response to a

drive force; a substrate having a conductor pattern for conveying a drive signal from a drive circuit; a piezoelectric vibrator provided on the substrate for undergoing oscillating movement in response to the drive signal so as to contact the movable member and generate the drive force to drive the movable member; and a support member provided on the substrate for mechanically supporting the piezoelectric vibrator on the substrate and transmitting the drive signal from the conductor pattern to electrodes of the piezoelectric vibrator so that no conductor wires extend from the substrate to connect the drive circuit and the piezoelectric vibrator; wherein the piezoelectric vibrator is a laminated structure comprising one or more piezoelectric elements polarized to undergo expansion-and-contraction vibration in response to the drive signal and one or more piezoelectric elements polarized to undergo flexural vibration in response to the drive signal so that a side face of the piezoelectric vibrator adjacent to the movable member undergoes elliptical movement in response to the drive signal to drive the movable member.

**ADDITIONAL FEES:**

A check in the amount of \$168.00 is enclosed to cover the cost of 2 independent claims in excess of 3. Should the check prove insufficient for any reason, authorization is